

Dear Customer,
Congratulations and thank you for purchasing an Arto Design product.



Prior to installation it is important to unpack and inspect all items to be installed to ensure that no damage has occurred during transit and that the item is correct before installation. If there are any visible defects DO NOT PROCEED WITH INSTALLATION.

No claims for damage will be recognized after installation.

INSTALLATION INSTRUCTIONS

BASIN/TOPS

1. Prior to installation remove the basin from carton and inspect for damage, or Faults.
2. Use the basin as a guide to mark the bench top for the tap and waste outlet positions. Cut out the required shape as marked (allow room for the plug & waste back nut, see also tapware installation instructions).
3. Install waste to the basin, using sanitary grade silicone as needed. Do not over-tighten waste, this is a major cause of cracking in the glazing of basins.
4. Install the tapware to the basin (if required), referring to the tapware installation instructions. Please ensure Tapware is properly fitted to Basin or Vanity Top ensuring the seal at the base of the Tapware is centered around the Tap Hole, it is recommended that silicone be used to create proper seal under Tapware. (Most water leaking into cabinets below have been found to be improperly installed tapware, with water running from the basin surface under the Tap)
5. Dab 2 x 5 cent piece size dollops of neutral cure, mildew resistant, sanitary grade silicone under a leading edge of the basin. Place the basin in position.
6. Connect the tapware to the hot and cold water service and the plug & waste to the waste pipe via an approved trap. Testing for leaks from Tapware, Wastes, & Overflow (if applicable)
7. Finish silicone on the surrounding leading edges (against the bench) using sanitary grade silicone. Clean away excess silicone from around the basin.

***Use of any other adhesives, and overuse of silicones will void warranty. (Epoxy Glues and overuse of silicone can stop the natural movement of the ceramic basin- expansion/contraction - and cause cracking in the basin).**

Nb. Standard manufacturing tolerances of vitreous china Basins & Tops are: +/- 0.5-2% . Standard Tap Hole variances on Arto Basins are 33-38mm Dia (Standard Tap Hole being 35mm)

Warranty:

Vanity Basins & Tops - Domestic	Warranty	Details
Ceramic	5/1 Years	5 Year Product Replacement 1 Year Labour
Poly Marble	5/1 Years	
Stone Bench	5/1 Years	
Timber Tops	5/1 Years	