#### ARTO Bathroom Ware



10-16 Lensworth St, Coopers Plains, QLD 4108
Tel: 07 3216 9666 | Fax: 07 3219 5533
www.arto.com.au | sales@arto.com.au

## Dear Customer,

# Congratulations and thank you for purchasing an Arto Design product.



Prior to installation it is important to unpack and inspect all items to be installed to ensure that no damage has occurred during transit and that the item is correct\*\* before installation. If there are any visible defects DO NOT PROCEED WITH INSTALLATION.

No claims for damage will be recognized after installation.

### **INSTALLATION INSTRUCTIONS**

#### BASIN/TOP

- 1. Prior to installation remove the basin from carton and inspect for damage, or Faults.
- \*\*2. Use the basin as a guide to mark the bench top for the tap and waste outlet positions. Cut out the required shape as marked (allow room for the plug & waste back nut).
- 3. Install waste to the basin, using sanitary grade silicone as needed. Do not over-tighten waste, this can cause cracking in the glazing.
- 4. Install the tapware to the basin (if required), referring to the tapware installation instructions. Please ensure Tapware is properly fitted to Basin or Vanity Top ensuring the seal at the base of the Tapware is centered around the Tap Hole. Apply sealant at the base of the mixer to ensure a water tight seal.
- 5. Dab 2 x small dollops of sanitary grade silicone under a leading edge of the basin. Place the basin in position.
- 6. Connect the tapware to the hot and cold water service and the plug & waste to the waste pipe via an approved trap. Testing for leaks from Tapware, Wastes, & Overflow (if applicable).
- 7. Finish silicone on the surrounding leading edges (against the bench) using sanitary grade silicone. Clean away excess silicone from around the basin.
- \*Use of any other adhesives, and overuse of silicones will void warranty. (Epoxy Glues and overuse of silicone can stop the natural movement of the ceramic basin- expansion/contraction and cause cracking in the basin).

Nb. Standard manufacturing tolerances of Ceramic Basins & Tops are: +/- 0.5-2%. Standard Tap Hole variances on Ceramic Basins are 33-38mm Dia.

### Warranty:

wulltuney.		
Vanity Basins & Tops - Domestic	Warranty	Details
Ceramic	5/1 Years	
Poly Marble	5/1 Years	5 Year Parts Replacement
Stone Bench	5/1 Years	First Year Labour
Rock Tops	5/1 Years	

\*\*Please note: Due to the nature of ceramic products, variations in size and shape do occur. The measurement of the purchased basins *must* be checked BEFORE cutting any countertop. Arto will not be liable for any errors other parties make when cutting countertops.